

5

DNA-BRIDGED CARBON NANOTUBE ARRAYS

This application claims priority to Provisional U.S. Application Serial No. 60/260,758 filed on January 10, 2001.

FIELD OF THE INVENTION

The present invention relates to carbon nanotube devices. More particularly, it relates to carbon nanotube chemical and biological sensor devices.

BACKGROUND OF THE INVENTION

The ability to detect chemical and biological species rapidly with specificity and at very low concentrations is becoming increasingly important, particularly in the medical, environmental and forensic areas. Detection of low levels pathogenic species such as agents that pose a biological threat, for example, provides a crucial measure of environmental contamination by such agents since their existence, even at low concentrations, can have serious pathological consequences. Sensitive detection devices therefore, enables the elimination of such pathogens prior to their causing significant harm. There is also a growing need for the rapid and quantitative detection of biological species in a number of biomedical applications, and the healthcare and food industries.

Chemical sensors disclosed in the art commonly utilize solid semi-conductor materials such as metallic oxides as sensor probes. Detection of target species by these sensors is typically accomplished by measuring a change in electrical resistance or optical property of the probes caused by adsorption of the species on the probe material surface. To provide adequate sensitivity however, such sensors have to operate at elevated temperatures to cause an increase in

5 chemical reactivity of the target species to the probe surface. Other limitations of prior art probes include long recovery times, poor specificity and reproducibility, and their inability to be specifically adapted for detection of a wide range of chemical and biological species.

Biological sensing devices offer the potential for providing high a degree of specificity and good sensitivity, but remain largely unexplored due to technical and chemical issues
10 pertaining to their structure-property characterization. Although charge transport properties of certain macromolecules such as DNA have been studied, their application as sensors has not been explored. This may be attributed to the inadequate understanding of the nature of the intrinsic properties of DNA, which has proven difficult to study directly using presently available systems.

15 Nanotechnological approaches to molecular electronics ("molelectronics") although theoretically feasible for sensor applications on the other hand, has not been practically realized mainly because they require materials with programmable structural and electronic characteristics.

In view of the above, there is a need for sensing devices that provide a highly sensitive
20 and specific response to target species requiring detection, but more desirably, provide a tunable response to a variety of chemical and biological species that pose pathological hazards to the environment.

OBJECTS AND SUMMARY OF THE INVENTION

The present invention comprises biological sensing devices that include a substrate
25 comprising an array of carbon nanotubes (CNTs) grown on a catalyst material deposited on the

5 surface of a non-metallic material, to which are chemically attached biological molecules. The
attached biological molecules are capable of electrical conductivity that is responsive to chemical
changes occurring in said molecules as a result of their interaction with target species that they
are designed to "sense" and detect. In particular, the invention biosensors based on the intrinsic
property of electrical conduction present in nucleic acids such as DNA and RNA and methods
10 for fabricating them.

The present invention provides a means for using DNA as a material of potential in
molecular electronic sensor devices, being primarily based on molecular electron-transfer
reaction processes between DNA-binding donors and acceptors. The π -stacked array of aromatic
heterocycles at the core of the double-helical structure of DNA mediate strong electronic
coupling between bound molecules. The integrity of the base stack of DNA is critical for
15 efficient charge transport, as the presence of disruptions in π -stacking brought about by mis-
paired bases or unpaired bases, and other external factors that perturb the base stack severely
attenuates DNA-mediated reactions. Unlike conventional methods of monitoring the intrinsic
electrical properties of DNA using conductivity measurements that are inconsistent, and wherein
neither variation of the length or sequence of the DNA, nor the points of electrical contact along
20 the DNA helix are well-defined, the present invention provides a means of measuring the
conductance of synthetic DNA assemblies, and their incorporation into molecular electronic
devices.

The present invention also provides methods for incorporating DNA assemblies
25 synthetically into molecular electronic devices and for measuring their electrical conductivities.
Using nanofabrication techniques, three-dimensional CNT arrays capped with gold are

5 constructed on a surface and subsequently functionalized chemically with DNA molecules. The
ability to “wire” sequences of synthetically defined composition chemically into nanoelectrodes,
enables systematical address, at an unprecedented level of detail, based on the influence of DNA
structure, sequence, and length on conduction. The sensor devices of the invention utilize the
capability of double-stranded DNA to conduct electricity, provides the means to measure the
10 electrical conductivity, and more importantly, changes in electrical conductivity in short (<100
bp) and specific DNA sequences. Sensors of substantially high sensitivity and portability are
therefore obtainable. The ability to measure extremely small changes in electrical conductivity
in the sensors of the invention is superior to conventional methods used for detecting DNA
sequences employing optical methods, such as by laser confocal fluorescence microscopy,
15 thereby rendering them suited for detection and quantitation of extremely low levels of the target
species. Furthermore, the sensors of the invention are adaptable to conventional silicon chip
technology, whereby sensing can be performed off the chip surface. The extra-surface detection in
the sensor devices of the invention is achieved by precise placement of electrically conducting
CNTs on lithographically-prepared substrates, wherein electrical connections between pairs of
20 carbon nanotubes is completed by target DNA strands complementary to probe DNA strands that
are previously set in place. Electrical connectivity between the CNTs and the DNA molecules is
achieved via the directed-assembly of DNA molecules onto gold coated CNT's via thiol linkers.
Sensors of the present invention have the ability to detect ultra-low levels of a variety of
biologically relevant pathogens in air, soil and water samples, and may be configured as a
25 miniaturized, portable device.

The present invention also provides a means for measurement of electrical conductivity
of DNA in sensors containing it, and enables the detection of specific DNA sequences, such as

5 those belonging to pathogenic target species. Such pathogen DNA sensors of the invention
comprise of DNA circuits wherein nanoscale electrical leads are constructed by incorporating
individually addressable multi-walled CNTs. A critical aspect of this design involves the
attachment of a metallic gold layer (either as a spherical nanoparticulate or as a coating) to the
tips of the individual nanotubes provide an anchoring surface for the DNA molecules. The gold
10 surface on the nanotube tips enables the immobilization of thiol modified DNA sequences via
spontaneous self-assembly. The sensors of the invention comprise of an array of pairs of
closely-spaced, individually electrically addressable CNTs comprising a terminally capped
metallic gold layer on their terminal ends. Pathogen sensors of the invention include DNA
circuits functioning as nanoscale electrical leads comprising individually addressable multi-
15 walled CNTs. A critical aspect in the sensor design involves the attachment of one or more gold
layers either as a coating or as a nanosphere particle to the tips or terminal ends of the nanotubes
which act as intermediaries between the nanotubes and the DNA molecules. The introduction of
a gold surface facilitates the immobilization of DNA sequences by self-assembly. Attached to
each sphere in a pair of CNTs will be multiple copies of a particular sensor strand. Introduction
20 of DNA that is complementary to the sensor strands on adjacent CNTs, causes an electrical
connection to be formed between the nanotubes. A complete sensor device of the invention has
a library of sensor sequences that are either individually or in specific groups unique to particular
targets, such as for example, pathogens. Since each pair of nanotubes can potentially be bridged
by multiple strands of duplex DNA, the total conductivity depend on the concentration of DNA
25 complementary to the sensor strands. Thus, the device of the invention can be used for the rapid
detection, fingerprinting, and quantitation of DNA from pathogenic organisms.

5 The present invention utilizes previously known nanofabrication techniques to obtain three-dimensional CNT arrays capped with gold nanospheres that can be chemically functionalized with DNA. The ability to “wire” sequences of synthetically defined compositions of DNA chemically into nanoelectrodes enables systematical addressing at unprecedented levels of detail, and enables the monitoring of the influence of DNA structure, sequence, and length on
10 electrical conductivity. The CNT-based arrays of the invention therefore, provide well-defined systems for inducement of electrical conductivity in DNA, and establish the extent to which DNA can serve as “molecular wiring” in nanoscale electronic devices. Regardless of the absolute conductivity of DNA molecules, conductivity can be modulated through sequence and structural effects. This allows for the properties of DNA, which are amenable to extensive
15 synthetic manipulation, to be exploited to their fullest potential.

 The sensor attribute of the present invention relies on the sensitivity of DNA-mediated charge transport to base stacking. Since single-stranded DNA has a considerable amount of structural freedom, the stacking in such a molecule should not promote electrical conductivity; only the substantially more rigid, double-stranded DNA molecules are capable of conducting
20 electricity. Thus, if a single-stranded DNA molecule is used as a molecular wire between two electrical contacts, no conductivity would be measurable unless until a complementary strand of DNA hybridizes to the single strand to form a conductive duplex. Since only *complete* hybridization with a sensor strand results in electrical conductivity, the single strand of DNA that “wires” together two electrical CNT contacts forms an extremely sensitive and highly selective
25 electrical sensor. Alternatively, a complementary strand can be used to link two initially unattached sensor strands to form a single, conductive duplex in a system in which no conductivity is possible. This results in enhanced sensitivity, since the conductivity of a DNA

5 molecule is substantially higher than that of a vacuum. A measurable response is therefore obtainable with such configurations that is independent of the intrinsic conductivity of DNA.

10 The use of CNT arrays as a structural support for the DNA based sensor devices of the invention is essential to the "sensing" attribute of the device. The measurement of electrical conductivity requires that only the ends of sensor DNA strands be in contact with the electrical leads. By immobilization of DNA probe sequences on gold spheres attached to CNTs, short-circuiting resulting from contact between intervening regions of the DNA bridge and the electrode surface is minimized. The use of a three-dimensional array of CNTs will also orient the resultant sensor probe sequences of the invention favorably (head-to-head) for hybridization with an incoming target sequence, and offers a distinct advantage over conventional metal nanoelectrode flat arrays which cannot present incoming sequences with such an orientation. The DNA immobilized CNT arrays of the invention can be used for fabricating electrically addressable DNA chips, for incorporation into electrical DNA biosensors with high-throughput capability.

20 The DNA sensor arrays of the invention are also compatible with conventional technologies for fabricating electrically conducting nanocircuits, such as etched trenches in silicon or surface deposition of thick nanowire contacts. The utilization of CNTs as electrical leads and "off-surface" supports for the sensor arrays of the present invention however, provides several advantages over these conventional methods. In the trench version, etch grooves may be employed to form a trench beneath and between the ends of two surface-deposited nanowires, with these now partly suspended ends subsequently linked by conducting DNA strands.

However, this process is unreliable and complex, with poor uniformity of the electrode gap, and severe problems with the nanoscale etching. Using thick electrodes for isolation of the DNA

5 contacted region from the surface, on the other hand introduces problems such as difficulty in obtaining (and maintaining) electrode gaps of the right magnitude (~10 nm) as the metal electrode thickness increases. Such limitations may be overcome by using methods that produce electrode gaps on the sub-10 nm scale using a combined electromigration/break-junction technique. Non-uniform gaps that are separated from the substrate by only 10-15 nm. The
10 present invention uses electron beam lithography and lift-off to produce reliably electrodes with separation gaps under 10 nm. The method of the invention allows to reproducibly prepare sets of nanoelectrodes with sub-10 nm gaps (*vide infra*) (down to 6 nm if required), and then grow CNTs at the ends of these electrodes to any height desired. DNA strands will then link the tops of these CNTs.

15 It is a principal object of the present invention to provide chemical and biological sensor devices that are capable of rapid and specific detection of extremely low levels of chemical and biological agents, particularly agents that pose a pathogenic hazard to the environment.

It is another object of the invention to provide a method for fabricating a new class of biosensors based on an intrinsic property of nucleic acids, namely, their electrical conduction.

20 It is another objective of the invention to provide synthetic assemblies of electrically conducting nucleic acids, including DNA assemblies, on a substrate surface, and their incorporation in molecular electronic devices using a nano-fabrication technique so as to enable them to behave as molecular conductors in sensing applications.

25 It is another object of the invention to provide a method for anchoring nucleic acids on a substrate surface and rendering to be electrically conducting, thereby enabling use in molecular electrical circuits.

5 It is yet another object of the invention to provide carbon nanotube arrays substrate for anchoring nucleic acid substrates including DNA via chemical bonding.

 It is a further objective of the invention to provide carbon nanotube arrays wherein at individual nanotubes are at least partially coated with a metallic material which enables anchoring of nucleic acid molecules.

10 It is also an object of the invention to provide electrically nanoelectrical circuits containing nucleic acid anchored CNT arrays that are deposited on a semiconducting material, methods for their fabrication.

 It is also an object of the invention to provide a method for the detection chemical and biological species using the sensors of the present invention.

15 These and other objects may be accomplished by a method for adsorbing nucleic acids on to the surface of metallic layer such as gold that is deposited either as a coating or as a metallic particle on individual nanotubes of a CNT array, that includes the steps of thiolating the nucleic acid and depositing the thiolated nucleic acid on the gold coated CNT array for a sufficient time for formation of covalent chemical bonds between the sulfur and the gold. The CNT substrates
20 may be obtained growing CNT arrays on a catalyst containing surface by plasma-enhanced hot filament vapor deposition. The catalyst containing surface for CNT growth can be patterned on a material surface by e-beam so as to produce CNT "nanocircuits." As used herein, the term nucleic acid pertain to both DNA and RNA which may be used interchangeably, because the invention is applicable to thiolation and attachment of both molecules to gold coated CNTs. By
25 "thiolation" is meant the incorporation of a thiol or mercapto (SH) group by chemical derivatization of the nucleic acid to give the corresponding thiolated nucleic acid Nu-SH, and

5 enabling their subsequent attachment to the gold coating on the CNT arrays by formation of Au-S-Nu type covalent bonds.

BRIEF DESCRIPTION OF THE FIGURES

10 **Figure 1** shows a schematic depiction of the DNA containing CNT “sensor” array of the invention. DNA “sensor” sequences are bound to particulate gold spheres at the tips of electrically addressed CNTs. Complementary DNA strands from a pathogenic genome fragment (target species) complete a circuit between adjacently paired nanotubes.

Figure 2 shows Au-coated polymer microspheres.

15 **Figures 3** shows SEM micrographs of CNT configurations of the invention (a) relatively short, decapitated nanotubes (b) nanotubes with a diameter of about 100 nm in a lithographically-defined array and (c) a patterned array of CNT nanotubes.

Figure 4 shows a schematic of process for preparation of silicon substrates and growth of CNTs terminated by gold nanoparticles.

20 **Figure 5** shows metal leads separated by a distance d varied from -10 to -100nm , each lead containing a Ni nanodot catalyst for growth of a multi-walled CNTs and nanotube pairs linked by complementary DNA sequences.

Figure 6 shows the derivatization of DNA oligonucleotides at (a) the 5'-terminus or (b) 3'-terminus by reacting an activated derivative of 4-mercaptobenzoic acid with a 5'- or 2'- amine on the terminal ribose, respectively.

5 **Figure 7** shows the fabrication and wiring of DNA-CNT arrays of the invention. The ends of the
electrically addressable nanotubes in the array are (a) etched and functionalized with thiols (b)
Gold-coated spheres are subsequently self-assembled to the tubes and (c) DNA sequences with
thiol linkers are directed to selected spheres by application of a voltage, and (c) resulting in an
addressable array of gold-bound DNA sequences; (d) strands of DNA that are complementary to
10 the sequences on adjacent spheres form a conductive path between the spheres.

Figure 8 shows two different configurations of the DNA-based biosensor of the invention for
detection of the presence of a pathogenic agent, (a) based upon a strand that links adjacent gold
spheres and (b) based upon two different sensor strands on adjacent spheres. In each case,
hybridization completes the electrical circuit between the spheres.

15 **Figure 9** shows the fabrication and wiring of DNA-CNT arrays of the invention where (a) ends
electrically addressable nanotubes are etched and functionalized with thiols (b) subsequent self-
assembly of gold-coated spheres to the nanotubes and (c) direction of DNA sequences with thiol
linkers to selected spheres by application of voltage to produce an addressable array of
goldbound DNA sequences.

20 **Figure 10** shows nanowires (about 210 nm wide Cr on Si) with separation gaps varying from
about 10nm to about 800 nm.

Figure 11 shows assemblies with different gold-DNA connectivities.

Figure 12 shows the introduction of perturbations in base stacking for determination of
conduction pathway and isolation of an intra-strand conduction path.

5 **Figure 13** shows a schematic of a second-generation device of the invention comprising a DNA-based FET.

Figure 14 shows a scheme for attachment of DNA to spheres that are electrically non-addressable.

10 **Figure 15** shows an SEM photomicrograph of a gold nanoparticle attached to the tip of a multi-walled CNT (both having a nominal diameter of about 121 nm) by the method of the invention.

Figure 16 shows the detection process of anthrax genomic sequences by monitoring DNA conductivity.

DETAILED DESCRIPTION

15 The fabrication of DNA-based electrical circuits of the invention comprising self-wiring DNA sensor arrays (shown in Figure 1) utilizes the following four distinct steps:

20 **1) Controllable creation of arrays of addressable multi-walled carbon nanotubes**

Arrays of paired, aligned CNTs, with nanotube proximity of about 100 nm in each pair are grown on a substrate surface to a length sufficient for subsequently linking them with DNA strands as described below. At least a portion of the nanotubes are individually electrically addressable. In one embodiment, multi-walled CNTs are preferred, as they are, in general, conducting (with proper chirality) and rigid. Multi-walled CNTs are grown by the plasma-enhanced hot-filament chemical vapor deposition method on a substrate. In another embodiment, the substrate is an e-beam patterned substrate.

2) The fabrication of smooth, gold-coated spheres of controllable dimension.

5 The present invention discloses a method that allows for the fabrication of smooth, gold-coated spheres of controllable diameters that range from about 100 nm to about hundreds of μm . Figure 2 shows the micron-scale gold-coated spherical beads prepared by this method.

(3) **The self-assembly of gold particles onto the ends of functionalized nanotubes.**

10 The nanotube ends in CNT arrays are selectively etched by a combination of nitric and sulfuric acid treatments. The etching process converts the carbon atoms on the ends of the tubes into carboxylic acid groups, which can then be reacted with amine-containing molecules to place any functionality desired at the tips of the tubes. For purposes of self-assembly, conductive, thiol-containing molecules are attached to the carboxylic acid groups, after which gold-coated particulates (such as the beads) can be self-assembled onto the tips of the tubes. This method of the invention enables the attachment of gold nanoparticles to single-walled CNTs, and can be utilized for the attachment of larger gold spheres to multi-walled tubes.

(4) **The self-assembly of DNA onto gold surfaces, and the subsequent ability of assembled DNA (when double-stranded and defect free) to conduct electricity.**

20 DNA molecules conjugated to a thiol-terminated linker are utilized to enable self-assembly on gold surfaces. The density of molecules adsorbed may be controlled either by manipulation of solution deposition conditions or surface bias. Two different single-stranded DNA sequences can be bound to neighboring spheres, following which
25 hybridization with a strand that is complementary to both initial strands completes the electrical circuit.

5 The present invention utilizes the above methods in concert, as a novel means for
creating selfwiring nanocircuits. The fabrication of the CNT arrays, the preparation of the gold-
coated spheres, the synthesis of DNA sequences with thiol linkers, and the assembly and wiring
of the DNA arrays as described below. The methods of the invention enable (i) construction of
DNA-CNT simplified arrays (first generation devices) for characterization of the electrical
10 behavior of bound DNA in the arrays, (ii) fabrication of DNA “wires” to form electrical
components (second generation devices) (iii) devices that combine wires and electrical and / or
electronic components to provide functional circuits (third generation devices), and (iv)
enhancement of such circuits to optimize their miniaturization (fourth generation devices).

Fabrication of electrically-addressable carbon nanotube arrays

15 Fabrication of addressable CNT arrays utilizes both micro- and nanolithographic
preparation of CNT catalyst sites and metallic addressing wires on single crystal silicon wafers.
Subsequently, growth of aligned CNTs on the catalyst surface is accomplished via hot filament,
plasma-enhanced chemical vapor deposition (hereinafter referred to as PECVD). Essentially, a
series of thin gold wires are defined lithographically on the silicon, wherein the inner ends of
20 pairs of individual wires are in close proximity (~100 nm). A CNT growth catalyst (e.g., nickel
(Ni) or cobalt (Co)) nanodot site is defined at these proximal ends using e-beam lithography,
following which the catalyst material is deposited. The wafers are then placed in a chemical
vapor deposition (CVD) chamber following which CNT growth is initiated, whereupon the CNT
growth occurs only at the catalyst nucleation sites. At this stage, the gold wires are passivated
25 using electropolymerization.

Typically, CNTs grown by this method are capped by a catalyst nanoparticle that is removable by nitric acid. The process of the invention omits the acid treatment step and thereby retaining the catalyst nanoparticle, which assists the subsequent attachment of thiol-linked gold nanoparticles, as described in C) and E) below. Additional control steps can be introduced into the process of the invention to obtain CNTs of uniform height within the arrays. Depending on growth conditions (which in turn, are dependant on properties of the catalyst), nanotubes in an array in a given growth run can vary in height between about 10% to about 50% (Figure 3). In order to maintain height uniformity which is essential for the successful electrical linkage of CNT pairs by DNA, the polymer fill is followed by mechanical polishing steps. Figure 4 shows the complete CNT array preparation process of the invention.

Important parameters in the process of the invention that are variable include the separation distance between pairs of wires (and therefore, between pairs of CNTs), the size (diameter and height) of the catalyst nanodot that nucleates the CNT growth and the catalyst deposition method. With a DNA base pair (bp) separation distance being of about 0.3 nm, a 100 bp sequence is about 30 nm long. Since the minimum feature size in state-of-the-art electron beam lithographic equipment is about 30 nm, a device preparation limit of 100 bp is in the acceptable range. The method of the invention can be used to grow multi-walled CNTs with nanotube diameters that are controllable down to about 100 nm. The smaller sizes required by the ~100 bp sequences of the invention can be obtained by using aligned CNT arrays of single-walled nanotubes. Figure 5 shows nanowires with various separation gaps obtained by the process of the invention.

The method of the invention utilizes two different methods of catalyst deposition. The first one involves a conventional e-beam evaporation of metallic nickel or cobalt following an e-

5 beam lithography step that defines the catalyst sites in an e-beam resist. This is followed by a lift-off step (of the unwanted catalyst material), leaving only the nickel or cobalt nanodots on top of the gold leads. The second method employs the self-assembly of catalyst nanoparticles from a catalyst-containing solution, which provides the advantage of eliminating the lift-off step in the process. In both cases, electrically addressable pairs of CNTs with well-defined heights and
10 lateral separations are obtained that amenable for subsequent attachment of intermediary particles necessary for surface immobilization of DNA sequences.

C. Preparation of gold-coated beads

15 The method of the invention utilizes commercially available monodisperse, chemically-functionalized polymer spheres ("beads") with diameters as small as about 100 nm. In a preferred embodiment, amine-functionalized beads are used for gold coating. Disubstituted compounds containing both thiol and carboxylic-acid functionalities are bound chemically to the beads using amide-coupling chemistry specific for carboxylic acid groups. Subsequent immersion of the beads in a suspension of gold nanoparticles results in self-assembly of gold nanoparticles onto the bead surface. Diffusion of the nanoparticles into the beads is precluded by
20 the relatively small pore size of the polymeric beads; the self-assembly reaction is, therefore, surface-specific. After a single layer of gold nanoparticles has been deposited on the bead surface, the gold layer can be built up by a serial repetition of the above steps. In another preferred embodiment the initial layer of gold nanoparticles can be grown to a predetermined layer thickness by electroless deposition of gold. Both processes can be used to "tune" the
25 coated sphere diameters to a predetermined value.

5 Synthesis of DNA sequences with thiol linkers

The attachment of DNA oligonucleotides to gold nanospheres by the method of the invention utilizes linkers that impart the shortest connectivity and provide the highest level of conjugation so that measured electrical conductivities correspond closely to DNA, and not to the properties of the linker. In a preferred embodiment, the coupling method involves a solution-
10 phase reaction between 4-mercaptobenzoic acid and a terminal amine either at the 2' or 5' position on the ribose moiety (Figure 6). This method provides a highly conjugated path between the gold particle and the DNA base stack. The incorporation of an amine at the 2' or 5' position is accomplished during chemical DNA synthesis by using commercially available reagents. A 2'-derivatization orients the DNA away from the gold surface when the linker is
15 placed at the 3' end of an oligonucleotide, while the 5'-derivatization provides the correct orientation for an oligonucleotide linked at the 5' end.

In another preferred embodiment, linker conjugation is achieved by the attachment of 4-mercaptobenzoic acid with a 5' pendant alkyl-amine or the incorporation of a short alkanethiol linker to the 3' end of DNA using a commercially-available reagent. These linkers give rise to
20 more intervening σ -bonds between the gold surface and the DNA base stack, and can be used in when a more insulating linker is desired, such as for example, in the construction of a single-electron transistor of the invention.

Assembly and wiring of DNA arrays

Assembly of "self-wiring" DNA arrays of the invention in which all of the CNTs are
25 electrically addressable is shown in Figure 7. The assembly process utilizes the array of electrically addressable CNTs prepared by methods of the invention described previously. In a

5 preferred embodiment, the catalyst plug at the end of the CNTs is removed by etching the
nanotubes in a combination of nitric and sulfuric acids, which in turn, leaves free carboxylic-acid
groups at the ends of the nanotubes. The electrical contacts to the nanotubes are protected from
the acids during the etching step. The carboxylic-acid groups at the nanotube ends are then be
reacted with electrically conductive, thiol group containing compounds, such as for example, *p*-
10 amino-thiophenol, utilizing standard amide-coupling chemistry. Gold nanoparticles or gold-
coated spheres are then self-assembled to the ends of the tubes (Figure 8).

The assembly of the CNT array is completed by one of two different synthetic
approaches. In a preferred embodiment, gold-coated spheres with pre-deposited single-stranded
DNA sequences are attached selectively to the CNTs. The negative charge of DNA molecules,
15 enables control of the attachment of spheres with a given DNA sequence to CNTs chosen
electrically. For example, negatively-biased nanotubes do not bind the gold beads, whereas
positively-biased nanotubes do. By sequential controlling the self-assembly reaction with beads
containing different DNA sequences, predetermined DNA-CNT arrays can be fabricated.

In another preferred embodiment, the DNA is bound to gold-coated spheres after the
20 spheres are attached to the CNTs in the array. This method provides post-attachment ability to
adjust the spheres sizes. Sphere sizes can thus be reduced via acid etching or increased via
electroless deposition. After spheres are attached to the nanotubes, potential differences are used
to control selective attachment of single-stranded DNA sequences to spheres containing thiol
linkers. In particular, self-assembly of the negatively-charged DNA to the spheres occurs readily
25 under positive bias, but not under sufficient negative bias. Figure 9 shows a schematic
illustration of the process.

5 After assembly of the DNA-CNT arrays is complete, “wiring” a pair of neighboring spheres together is accomplished by subjecting the array to single-stranded sequences that are complementary to the different sequences on the two spheres. Hybridization completes the circuit between the beads. Although significant conductivity may be observed even for one double-stranded DNA connection between two beads, each connection is likely to be composed
10 of hundreds of individual wires. The DNA-CNT arrays of the invention can be characterized by atomic force microscopy using standard analytical methods.

First generation DNA-CNT array devices

First generation of devices of the invention enables optimization of the fabrication, wiring and assembly procedures of the DNA-CNT arrays, and characterization of the electrical
15 properties of DNA. First generation devices consist of two parallel rows of electrically-addressable nanotubes with spheres containing various single-stranded DNA sequences assembled to the ends (Figure 10). Arrays are designed to enable optimization of the following:

Device Fabrication: Optimization of reproducibility and fidelity of the CNT arrays that host the DNA, can be accomplished by seeking the most appropriate set of parameters for
20 subsequent DNA strand attachment. Simple arrays of pairs of gold wires on silicon (specifically, about 70 nm gold (Au) atop about 10 nm titanium (Ti), on an approximately 90 nm silicon nitride (Si_3N_4) LPCVD-grown layer on silicon (Si) is preliminarily used. These are first defined by conventional (UV) photolithographic techniques in a Au-wire pattern of that will include the appropriate placement marks for the subsequent e-beam lithography step, wherein pairs of
25 smaller Au wires can be defined, leading from the initial macroscale wires toward each other in the center of the wafer. The separation gap d between the termini of these leads can be initially

5 varied in this first generation device from about several hundreds of nm to about the 50 to 100 nm range. As shown in Figure 10, this is followed by a second e-beam lithography stage that defines the positions of the nickel or cobalt catalyst sites placed at the ends of the gold nanowires.

Device Assembly: Determination of the appropriate voltages for directing the self-assembly of

10 Au-coated spheres onto selected nanotubes is essential for device assembly. Due to the enhanced electric field at the tips of the nanotubes, these voltages are likely to vary with the diameters and lengths of nanotubes. Likewise, it is necessary to optimize the conditions under which DNA can be deposited on selected spheres with the desired efficiency and reproducibility. Selective tagging and fluorescence microscopy is used to characterize the arrays at each step of the device assembly procedure. For instance, to determine the positions of the gold spheres, a thiol-containing fluorophore, such as the product of the reaction of dansyl chloride with *p*-aminothiophenol, is used to “stain” these portions of the device selectively. Similarly, fluorescently-tagged sequences of complementary DNA is be used to determine the positions of each specific sequence that has been included in the array. Additionally, fluorescently-labeled
15
20 bridging sequences and/or fluorescent probes that bind specifically to duplex DNA is employed to confirm that the desired “wiring” pattern has been achieved upon the addition of the bridging sequences.

Electrical properties of DNA:

In a photoinduced charge transfer between DNA bases, a path that is restricted to one
25 strand of the DNA double helix prompts the most efficient transfer. Electron migration across

5 the hydrogen-bonded strands slows rates of charge transfer and increases the dependence of the rate of electron transfer on distance.

The device of present invention contains individual single strands of DNA that are attached to nanoelectrodes, whereby the contacts may be varied to determine whether both ends of an individual DNA strand involved in a bridging double-stranded helix must be in electrical
10 contact to obtain efficient conduction (Figure 11). Furthermore, devices of the invention can be tested in two assembly types (i) assemblies featuring one DNA strand attached to two gold nanospheres through Au-S linkages at both the 3' and 5' ends of oligonucleotides comprising the same strand. The complementary strand is then attached only through non-covalent interactions (these assemblies will be referred to with the abbreviation 3'-5'), and (ii) assemblies featuring
15 one end of each strand of the double helix attached to gold (abbreviated as either 3'-3' or 5'-5'). Higher levels of conductivity observed for the 3'-5' assembly indicate that electron flow along one side of the double helix is most efficient. Comparable conductivities for the 3'-5', 3'-3', and 5'-5' assemblies indicate that electron flow proceeds through the double helix as a whole.

Base-pairing and perturbations in base stacking: This method helps establish that the
20 currents observed are DNA-mediated in the device of the invention. Figure 12 shows the perturbations introduced in base stacking within the double helix as a means of interrupting the conduction path. Since electron transfer between molecular donors and acceptors mediated by DNA shows that electronic coupling is severely attenuated in the presence of single-base mismatches that disrupt the integrity of the π -stack. The effects of mispaired bases on the
25 conductivity-based assay can therefore, be measured.

5 It is desirable to limit the conduction path to one strand of the double helix. This is accomplished by engineering Au-S connectivities as described previously for the 3'-5' assembly, whereby intrastrand conductivity can be forced by disrupting the stacking in the strand that is not covalently linked to the gold microspheres. As shown in Figure 12, disrupting the base stacking only in one strand can potentially be accomplished through the incorporation of 3-way helical
10 junction, or by base mismatches perturbing stacking of the bases such as, for example, in a pyrimidine rich strand over a purine-rich strand. Systematic control over the path of current flow through DNA molecules can be therefore, utilized to design molelectronic devices with specific performance requirements.

DNA length: DNA conductivity in the device of the invention is performed with first-
15 generation CNT arrays by systematic variation of the length of the DNA sequence serving to bridge two nanotubes. In a preferred embodiment, the nanotube spacing is engineered at the level of catalyst deposition, that allows variations in spacing from about 10 nm to about 210 nm. In another preferred embodiment, the size of the capping gold micro-spheres is varied, thereby allowing spacing variations to less than about 10 nm. This distance range permits conductivity
20 measurement in sequences of ranging from 30 to 500 base pairs.

DNA sequence: DNA bases vary significantly in redox potential. The purine bases exhibit electrochemical reduction potentials (versus nickel hydride electrode (NHE)) of -2.8 V (G) and -2.5 V (A), and oxidation potentials of +1.5 V (G) and +2.0 (A). The pyrimidines are more easily reduced than the purines (-2.4 V (C) and -2.2 V (T)), but are more difficult to
25 oxidize (+2.1 V (C) and +2.2 V (T)). These differing potentials give rise to detectable effects in the conductivity of DNA molecules of different sequences.

5 The method of the invention employs the synthesis and immobilization DNA sequences of varying composition to measure conductivity variations. The ability to effectively “shut down” one strand of the DNA helix by manipulating connectivity or by introducing base-stacking perturbations in the devices of the present invention. For example, if conductivity relies only on the bases within one strand, a sequence composed only of cytidine and thymine can be compared to one containing only guanine and adenine. If conduction cannot be limited to an intrastrand pathway, sequences containing only GC base pairs can be examined and levels of conduction to sequences containing only AT base pairs can be compared.

10 In a preferred embodiment, unnatural bases are incorporated into bridging DNA sequences. For example, the higher electron affinity of 5-iodo-cytosine or the lower electron affinity of 5-methyl-uracil alters the voltage-current profiles obtained. The conductivities of sequences of varying composition are evaluated and correlated with the values obtained with the electronic properties of the intervening monomers, thereby enabling engineering of variations in bridging sequences that will provide molecular resistors, diodes and transistors. In another preferred embodiment, silver-coated DNA is used to provide highly conductive connections.

20 **Second-generation DNA-CNT array devices**

Optimization of first generation parameters in the devices of the invention enables the fabrication of complex circuit elements based on DNA-bridged nanotubes, such as resistors, capacitors, diodes and transistors. For resistors, necessary control required for the design and fabrication resistors over a wide range of resistance can be accomplished. Given the relation $R = \rho \ell / A$ (where R = resistance, ρ = resistivity, ℓ = length and A = area), resistance can be varied through variations in: (i) ℓ , by controlling the length of the bridged DNA strands (i.e. varying the

5 separation between nanotubes) (ii) A, by controlling the number of double-stranded connections
between nanotubes; or (iii) ρ , by choice of appropriate base sequence (and redox potential)
within a connection. In addition, the base stacking perturbations described above can be
intentionally employed as defect sites to control (increase) the electrical resistance across a path.
Similarly, diodes can be created by choosing sequences with an appropriate spatial ordering of
10 bases with different reduction potentials.

A preferred embodiment of a nonlinear nanoscale devices (such as diodes and transistors)
of the present invention is shown in Figure 13. A pair of CNTs linked by a specific DNA
sequence act as the source and drain of a 3-terminal FET (field-effect transistor). The controlling
gate terminal is connected to the source/ drain sequence by the formation of a three-way
15 junction. When the bases across from the junction in the source/drain strand will remain stacked,
bases with a high reduction potential may be placed in these positions, such that this potential
can be modulated by placing a voltage on the gate. On the other hand, if base stacking is lost in
this region, synthetic bases that can then be aligned (and therefore stacked) in an electric field
may be chosen. In either case, voltage applied at the gate enables control of current along the
20 source/ drain path.

In another preferred embodiment, the device of the invention is a single electron
transistor (SET), wherein the main conduction process is by electrons tunneling across a tunnel
barrier. Figure 7 shows thiol linkers between a metal sphere atop the nanotube tip and the DNA
strands. By altering the chemical structure of these linkers (as shown in Figure 2), the electron
25 transport across these linkers can be tuned from conducting to insulating. In the non-conducting
configuration, these links act as tunnel barriers between metallic contacts and the DNA, and
perform the electron sensing function by themselves. The source and drain remain as shown in

5 Figure 13, but the gate electrode is not required. This results in new types of molectronic SET that function at room temperature, improved photon sensors, including in the ultraviolet, visible and infrared ranges, and Coulomb-blockade devices with a tunable negative differential resistance.

Third generation DNA-CNT arrays

10 Third-generation devices of the invention enable the fabrication of entire functional circuits. As shown in Figure 12, an important prerequisite in such circuits is ability of DNA to “wire” spheres on CNTs that are not initially electrically addressable, thereby allowing the creation of complete, self-wiring circuits.

15 Figure 14 shows a schematic representation of a preferred embodiment, wherein DNA strands with a free thiol at one end and a chemically-protected thiol at the other that are attached to an electrically-addressable sphere. To ensure the rigidity of these sequences, duplex DNA is used to preclude the strands from becoming hybridized with a complementary strand after attachment to the sphere. Subsequent chemical deprotection of the thiols at the unattached ends of the strands now permits them to attach to an unaddressed sphere that is within a proper
20 distance of the sphere of initial DNA attachment. At this point, the complementary strand is removed by thermal or chemical methods. If further connections to the unaddressed sphere are not required, then the single-stranded connection is retained as such, since the base-stacking necessary for conductivity occurs only in the presence of a complementary strand. On the other hand, to make further connections to this nanotube, a restriction enzyme can be used to cut the
25 strand at a predetermined position. Diffusion of linking thiols along the surfaces of the spheres will lead to an isotropic distribution of DNA around the unaddressed sphere over time. Ligation

5 of an appropriate sequence to the DNA on the unaddressed sphere allows for repetition of this to form connections to another unaddressed spheres.

Fourth-generation DNA-CNT arrays

The fourth generation of devices of the invention combine all of the advances made in the previous three generations, while providing the ultimate degree of miniaturization. It enables
10 fabrication of arrays of closely-spaced, electrically addressable *single-walled* CNTs of fixed chirality (i.e., conductivity). In a preferred embodiment, gold-coated spheres are replaced by monodisperse gold nanoparticles with diameters from about 10 nm to about 200 nm. The attachment of gold nanoparticles of controlled size to single-walled CNTs is essential the fourth-
15 generation device technology of the invention in order to reach an appropriate level of miniaturization. Figure 15 shows a gold nanoparticle about 121 nm in diameter attached to a multi-walled CNT of nominal diameter about 121 nm.

The factor that determines optimal feature size in such a device is the number of base pairs needed in a strand of duplex DNA to prevent melting under ambient conditions. At room temperature, this number is approximately 15, which requires to a minimum interconnect size of
20 about 5 nm. Practically, however, slightly longer sequences are employed to ensure availability of adequate sequence diversity to make a large numbers of unique, independently “wirable” connections. It is, therefore, possible to fabricate complex, self-wiring circuits with interconnect lengths on the order of about 15 nm and terminal sizes on the order of about 10 nm, which is substantially smaller than those obtained by current silicon-based lithographic techniques. In
25 addition to the unique capabilities of the DNA-based electronic devices of the previously

5 described generations of the invention, fourth-generation devices additionally offer significantly faster operation than standard microcircuits.

Conductivity-based DNA-CNT sensor device for microorganism detection

10 A sensor device of the present invention can be used for detecting DNA sequences found in the genome of pathological microorganisms, such as for example, *Bacillus anthracis* (anthrax), a lethal pathogen that is a dangerous agent because of facile dissemination through aerosolization (Figure 16). In a preferred embodiment a 150 nucleotide fragment of the genome of *B. anthracis* identified as a unique maker for this species is used in the analysis. A 50-nucleotide region of this fragment can be targeted that is sufficiently unique to “report” the presence of the species with a high degree of accuracy. Two adjacent CNTs can be bridged with a thiol-modified 50-base pair synthetic oligonucleotide that is complementary to the target sequence. Detection of the presence of the anthrax sequence can then be performed in the simplest possible sample, a purified 50-mer generated synthetically that corresponds to the target genomic sequence. The levels of conductivity in the presence and absence of the target sequence can be monitored to first establish that a differential response can be acquired. Based on known electronic properties of DNA, introduction of the complementary target sequence will present a molecular bridge with conductivity significantly elevated over the single-stranded bridge. Once this measurable conductivity increase resulting from the presence of the target strand is established, it will determine the detection limits for the DNA-CNT array sensor device of the invention, and monitor the kinetics of the hybridization events. Such analyses can be conducted under artificially simplified conditions to enable establishment of assay viability and for optimizing sensitivity.

5 In another preferred embodiment, the complexity of analyte sample is increased by using DNA produced in bacterial culture. The complete 150 nucleotide anthrax marker fragment previously identified is introduced into a plasmid that can be produced in *E. coli*. The presence of the targeted sequence in lysates containing different cell densities that will thereby contain different levels of plasmid DNA is assayed. This allows protocol optimization in the presence of
10 other DNA sequences and other components present in cellular extracts. Plasmid constructs are generated such that they incorporate larger segments of the anthrax genome in order to establish the effect of overhanging, non-hybridized sequences, or to encode similar regions of nonvirulent, closely-related species for establishing the ability of the sensor to discriminate against innocuous bacteria. After detection of DNA sequences with high accuracy and sensitivity is optimized, the
15 sensor device of the invention is used in field testing for anthrax.

The devices methods and processes of the invention can be used in biological sensing devices to sense and detect pathological biological species including microorganisms (such as anthrax), viruses, pathogenic biological molecules (such as toxins), enzymes, proteins, and chemical agents at extremely low levels with high specificity. The present invention can also be
20 used to fabricate multi-element DNA circuits for applications such as amplification, logic, and memory circuits. Additionally, such devices also allow the evaluation of the speed and performance of DNA-based circuitry. Potential applications of such circuits include sensors for specific DNA sequences with single-molecule sensitivity and DNA-based computers in which a DNA amplification step is not required.

25 The devices of the invention, including mechanical and chemical processes for their preparation, as well as methods their fabrication will become apparent to one familiar in the art based on the aforementioned embodiments and the following non-limiting examples.

5 **Example 1**

Controllable creation of arrays of addressable multi-walled carbon nanotubes

CNTs are grown by the plasma-enhanced hot filament chemical vapor deposition method, including on an e-beam patterned substrate. Metallic nickel, deposited via e-beam lithography over a non-catalytic metal provides the electrical leads, is used as the catalyst for CNT growth.

10 **Example 2**

Growth of controlled dimension gold-coated spheres

Gold-coating procedure of spheres utilizes the functionalization of microspheres with thiols groups to enable the self-assembly of metallic gold nanoparticles on functionalized sphere surfaces. The initially formed gold layer is subsequently built up either through sequential steps of linker addition followed by additional contact with gold nanoparticles, or through electroless deposition of gold on the functionalized sphere surfaces.

Example 3

Synthesis of DNA sequences with thiol linkers

The synthetic method involves a solution-phase reaction between 4-mercaptobenzoic acid and a terminal amine either at the 2' or 5' position on the ribose moiety. The incorporation of an amine at the 2' or 5' position is accomplished during chemical DNA synthesis using commercially available reagents. A 2'-derivatization is carried out to orient the DNA away from a gold surface when the linker is placed at the 3' end of an oligonucleotide, while a 5'-derivatization is done to orient the oligonucleotide linked at the 5' end. Alternatively 4-

5 mercaptobenzoic acid is reacted with a 5' pendant alkyl-amine or the incorporation of a short alkanethiol linker to the 3' end of DNA using a commercially-available reagent.

Example 4

Fabrication of electrically-addressable carbon nanotube arrays

10 The preliminary step involves a micro- and nanolithographic preparation of CNT catalyst sites and metallic addressing wires on single crystal silicon wafers. This is followed by growth of aligned CNTs via hot filament, plasma-enhanced chemical vapor deposition (PECVD). A series of thin gold wires lithographically on the silicon is defined, with the inner ends of pairs of individual wires in very close proximity (~100 nm). At these proximal ends, a CNT growth catalyst (e.g., Ni or Co) nanodot site is defined using e-beam lithography, and the catalyst material deposited. This wafer is then placed in the CVD chamber, with subsequent CNT growth occurring only at the catalyst nucleation sites. At this point the gold wires may be passivated using electropolymerization. If deemed necessary, additional steps can be introduced to obtain strictly uniform height of the CNTs in the arrays. Depending on growth conditions used, CNTs height in an array in a given growth run can be varied in height by 10% - 50%
15
20 Height uniformity is accomplished by performing additional mechanical polish steps.

Example 5

Catalyst deposition methods

Conventional e-beam evaporation of nickel (Ni) or cobalt (Co) is used after an e-beam lithography step is performed on the substrate to define the catalyst sites in an e-beam resist.
25 This is followed by a lift-off step (of the unwanted catalyst material), leaving only the Ni or Co

nanodots on top of the gold leads. Alternatively, a self-assembly of catalyst nano-particles from a catalyst-containing solution is used, which precludes the need for the lift-off step. In either case, at the end of this phase, electrically addressable pairs of CNTs with well-defined heights and lateral separations are prepared. Separations between nanotubes down to 10 nm, can be obtained reproducibly by these methods.

Example 6

Assembly and wiring of DNA-CNT arrays

The catalyst plug at the end of the CNTs array of electrically addressable CNTs obtained in Example 4 is removed by etching the tubes in a combination of nitric and sulfuric acids, to give free carboxylic acid groups at the ends of the CNTs. The electrical contacts to the tubes are protected from the acids during the etching step. The carboxylic-acid groups at the ends of the tubes are then be reacted with *p*-aminothiophenol using standard amide-coupling chemistry.

Gold nanoparticles or gold-coated spheres are then self-assembled to the ends of the tubes, following which single-stranded DNA is deposited on the coated spheres. The gold-coated spheres with predeposited single-stranded DNA sequences are then attached selectively to the CNTs. By a sequential control of self-assembly reactions with beads containing different DNA sequences, desired array can are fabricated. Alternatively, the DNA is bound to the gold-coated spheres after the spheres have been attached to the CNTs in the array. The sizes of the spheres are then adjusted if necessary, after attachment via acid etching (if smaller spheres are required) or electroless deposition (if larger spheres are required). Once the spheres have been attached to the CNTs, potential differences are used to control selective attachment of spheres single-stranded DNA sequences with thiol to other spheres.

5 CNT-supported DNA arrays of the present invention can be used in the development of a
new class of sensors that differ from those currently available in the degree of portability and
sensitivity. Many of the current methods for pathogen detection require the amplification of
DNA samples using the polymerase chain reaction (PCR), a powerful but target-specific and
time-consuming process. The nanoscale detector of the present invention is expected to be
10 effective at very low concentrations of DNA and may enable the direct analysis of aerosolized
agents collected from air. The transport of charge through DNA, it assays an intrinsic property
of DNA, not one imparted by a probe molecule and hybridization thermodynamics. This feature
will provide greater sensitivity and accuracy.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217